

# SP-275K-H1

## SP Series String Inverter



### More power generation

- Max. efficiency 99%, Euro efficiency 98.8%
- 12MPPTs for tracking maximum PV power
- Supports bifacial PV modules with max. PV current 20A



### High reliability

- Cooling fan with IP68 protection level
- Integrated string monitoring function
- Standard connection terminal for quick installation



### Low system cost

- Up to 24 PV strings
- Support aluminum cable access, saving cable costs
- Support PLC communication, save communication cable



### Grid friendly

- LVRT and HVRT function
- Active & Reactive power control

Model	SP-275K-H1
Input (DC)	
Max. PV input voltage	1500V
MPPT Max. input current	40A*12
Rated input voltage	1080V
MPP voltage range	500~1500V
MPP voltage range for nominal power	880~1300V
Number of MPPT trackers	12
Max. number of PV strings	24
Output (AC)	
AC output power	275kW@30°C/250kW@45°C/225kW@50°C
Max. output power	275kW
Rated grid voltage	800V
Grid voltage range	680~880V
Max. output current	198.5A
Rated grid frequency/range	50Hz/45~55Hz, 60Hz/55~65Hz
Output current harmonic (at nominal power)	<3%
Power factor at nominal power/range	>0.99/0.8leading to 0.8lagging
Protection	
DC reverse connection protection	Yes
Over voltage protection	DC Type II/AC Type II
Leakage current protection	Yes
Grid monitoring	Yes
Insulation monitoring	Yes
Anti-island protection	Yes
Efficiency	
Max. efficiency	99.0%
EU efficiency	98.8%
General Data	
Isolation method	Transformerless
Self-consuming in night	<3.5W
Protection level	IP66
Temperature	-30°C ~ +60°C
Allowed humidity (non condensing)	0-100%
Cooling mode	Temperature controlled forced air cooling
Max.operating altitude	4000m
Communication port	Standard: PLC, Optional: RS485
Certificates and approvals (more available on request)	CE, IEC 62109, IEC 61727, IEC 61683, IEC 62116, IEC 60068, IEC61000, IEC60529, EN50530, EN62920, EN50549, PO.12.2 NTS631, VDE 0126 VFR+UTE_C15-712-1, CEI 0-16, C10/11
Dimensions (W×H×D)	1180×733×350mm
Weight	130kg

## Circuit Diagram

