

# Si-Dongle Data Logger



## Efficient Management

Support up to 10 devices

## Flexible Networking

Support local & remote monitoring

## Easy Installation

Plug & play design

Model	Si-Dongle-S	Si-Dongle-T
<b>System information</b>		
Supported models	SN & SP Series	SN & SP Series
Max. connected devices	2 Units	10 Units
No. of LEDs	3	3
<b>Communication parameters</b>		
Communication method	WIFI	WIFI
User interface	APP/Web	APP/Web
Frequency	2.4GHz(a/b/g/n)	2.4GHz(a/b/g/n)
Data uploading interval	5 Mins(1-5 Mins configurable)	5 Mins ( 1-5 Mins configurable)
Smart access*	Support	Support
Other functions	Remotely parameters release & Firmware upgrade	Remotely parameters release & firmware upgrade
<b>Electrical parameters</b>		
Operating voltage	5-12Vdc	5-12Vdc
Power consumption	≤3.3W	≤3.3W
<b>General data</b>		
Dimensions (W*H*D)	50*116*35mm	50*116*35mm
Protection degree	IP65	IP65
Operating temperature	-30~60°C	-30~60°C
Operating humidity	0~95%	0~95%
Installation method	Plug & play	Plug & play
Certification	CE	CE

\*Smart access: The Data logger can automatically identify the accessed devices, and addressed the devices, no manual setup is required.